

TECHNICAL DATA

42.15 STEREO Power Output

Maximum power 70Wx2
Nominal RMS 4 Ohm, 1 kHz at 1% THD 45Wx2
Nominal RMS 4 Ohm, 20 Hz to 20 kHz at 0,05% THD 35Wx2

BRIDGED Power Output

Maximum power, 4 Ohm, 1 kHz 150W

42.17 STEREO Power Output

Maximum power 100Wx2
Nominal RMS 4 Ohm, 1 kHz at 1% THD 65Wx2
Nominal RMS 4 Ohm, 20 Hz to 20 kHz at 0,05% THD 50Wx2

BRIDGED Power Output

Maximum power, 4 Ohm, 1 kHz 200W

Frequency response +0, -1dB 10-50,000 Hz

S/N (signal to noise ratio) INFA-weighted 105 dB

Input sensitivity/Impedance

(for nominal power output)

Control in mid position 500 mV/10k Ohm
Variable control 100-2,000mV/10k Ohm

Speaker impedance 4 or 2 Ohm (stereo)
4 Ohm (bridged, mono)

Power supply (negative ground) 14.0V DC (11-16 V permissible)

Net Weight

42.15 1.3 kg
42.17 1.5 kg

Chassis size

42.15 150(L)x50(H)x217(P) mm
42.17 180(L)x50(H)x217(P) mm

Due to continuing improvement, the features and the design are subject to change without notice.