

TECHNICAL DATA

43.05 Maximum power	70Wx2
Nominal RMS 4 Ohm, 1 kHz at 0.08%THD	50Wx2
Maximum power - bridged configuration 10% THD	220Wx1
43.07 Maximum power	100Wx2
Nominal RMS 4 Ohm, 1 kHz at 0.08%THD	70Wx2
Maximum power - bridged configuration 10% THD	340Wx1
43.10 Maximum power	130Wx2
Nominal RMS 4 Ohm, 1 kHz at 0.08%THD	100Wx2
Maximum power - bridged configuration 10% THD	470Wx1
Frequency response +0, -1dB	10-50,000 Hz
S/N (signal to noise ratio) INFA-weighted	105 dB
Input sensitivity/Impedance (for nominal power output)	
Control in mid position	500 mV/10 kOhm
Variable control	100-2,000mV/10 kOhm
Low-Boost control at 45Hz	Off, +3dB, +6dB
Speaker impedance	4 or 2 Ohm (stereo) 4 Ohm (bridged, mono)
Power supply	14.4V DC (11-16 V permissible)
Net Weight	
43.05	2.15 kg
43.07	2.92 kg
43.10	3.65 kg
Chassis size	
43.05	280(W)x55(H)x150(D) mm
43.07	280(W)x55(H)x200(D) mm
43.10	280(W)x55(H)x250(D) mm

Due to continuing improvement, the features and the design are subject to change without notice.